

# Cuplas

## Cuplas, cuplas de reducción y medias cuplas para cañerías

Cuplas  
Cuplas de reducción  
Medias cuplas  
Cuplas

### Cuplas

**Tabla de cuplas de Serie 3000 - Roscado y SW**

Tamaño		A Roscado	B Roscado	A SW	B SW	C Min.	D Max.	E Max.
pulg.	mm	mm	mm	mm	mm	mm	mm	mm
1/8	3.20	16.00	32.00	17.00	28.00	10.00	10.90	7.60
1/4	6.40	19.00	35.00	22.00	28.00	10.00	14.35	10.00
3/8	9.50	22.00	38.00	25.40	29.00	10.00	17.80	13.30
1/2	12.70	29.00	48.00	31.70	33.00	10.00	21.95	16.60
3/4	19.00	35.00	51.00	38.10	39.00	13.00	27.30	21.70
1	25.40	44.40	60.00	44.40	43.00	13.00	34.05	27.40
1 1/4	31.80	57.00	67.00	57.00	43.00	13.00	42.80	35.80
1 1/2	38.00	64.00	79.00	64.00	43.00	13.00	48.90	41.70
2	51.00	76.00	86.00	76.00	55.00	16.00	61.35	53.50
2 1/2	63.50	92.00	92.00	92.00	56.00	16.00	74.20	64.20
3	76.00	108.00	108.00	108.00	56.00	16.00	90.15	79.50
4	102.00	140.00	121.00	140.00	62.00	19.00	115.80	103.80

**Tabla de cuplas Serie 6000 - Roscado y SW**

Tamaño		A Roscado	B Roscado	A SW	B SW	C Min.	D Max.	E Max.
pulg.	mm	mm	mm	mm	mm	mm	mm	mm
1/8	3.20	22.00	32.00	19.00	28.00	10.00	10.90	4.80
1/4	6.40	25.00	35.00	24.00	28.00	10.00	14.35	7.10
3/8	9.50	32.00	38.00	29.00	29.00	10.00	17.80	9.90
1/2	12.70	38.10	48.00	35.00	33.00	10.00	21.95	12.50
3/4	19.00	44.40	51.00	41.20	39.00	13.00	27.30	16.30
1	25.40	57.00	60.00	50.80	43.00	13.00	34.05	21.50
1 1/4	31.80	63.50	67.00	57.00	43.00	13.00	42.80	30.20

Tamaño		A Roscado	B Roscado	A SW	B SW	C Min.	D Max.	E Max.
pulg.	mm	mm	mm	mm	mm	mm	mm	mm
1 1/2	38.00	76.00	79.00	67.00	43.00	13.00	48.90	34.70
2	51.00	92.00	86.00	83.00	65.00	16.00	61.35	43.60
2 1/2	63.50	108.00	92.00			16.00	74.20	
3	76.00	127.00	108.00			16.00	90.15	
4	102.00	159.00	121.00			19.00	115.80	

Cuplas de reducción

## Cuplas de reducción

### Tabla de cuplas de reducción Serie 2000 y 3000- Roscado y SW

Tamaño	A Roscado	B Roscado	A SW	B SW	C Min.	D Max.	E Max.	F Max.
pulg.	mm	mm	mm	mm	mm	mm	mm	mm
1/4 x 1/8	19.00	35.00	22.00	28.00	10.00	14.35	7.60	10.90
3/8 x 1/4	22.00	38.00	25.40	29.00	10.00	17.80	10.00	14.35
1/2 x 3/8	29.00	48.00	31.70	33.00	10.00	21.95	13.30	17.80
3/4 x 1/2	35.00	51.00	38.10	39.00	13.00	27.30	16.60	21.95
1 x 3/4	44.40	60.00	44.40	43.00	13.00	34.05	21.70	27.30
1 1/4 x 1	57.00	67.00	57.00	43.00	13.00	42.80	27.40	34.05
1 1/2 x 1 1/4	64.00	79.00	64.00	43.00	13.00	48.90	35.80	42.80
2 x 1 1/2	76.00	86.00	76.00	55.00	16.00	61.35	41.70	48.90
2 1/2 x 2	92.00	92.00	92.00	56.00	16.00	74.20	53.50	61.35
3 x 2 1/2	108.00	108.00	108.00	56.00	16.00	90.15	64.20	74.20
4 x 3	140.00	121.00	140.00	62.00	16.00	115.80	79.50	90.15

### Tabla de cuplas de reducción Serie 6000 - Roscado y SW

Tamaño	A Roscado	B Roscado	A SW	B SW	C Min.	D Max.	E Max.	F Max.
pulg.	mm	mm	mm	mm	mm	mm	mm	mm
1/4 x 1/8	22.00	35.00	24.00	28.00	10.00	14.35	4.8	10.9
3/8 x 1/4	25.00	38.00	29.00	29.00	10.00	17.80	7.10	14.35
1/2 x 3/8	32.00	48.00	35.00	33.00	10.00	21.95	9.90	17.80
3/4 x 1/2	38.10	51.00	41.20	39.00	13.00	27.30	12.50	21.95
1 x 3/4	44.40	60.00	50.80	43.00	13.00	34.05	16.30	27.30

Tamaño	A Roscado	B Roscado	A SW	B SW	C Min.	D Max.	E Max.	F Max.
pulg.	mm	mm	mm	mm	mm	mm	mm	mm
1 1/4 x 1	57.00	67.00	57.00	43.00	13.00	42.80	21.50	34.05
1 1/2 x 1 1/4	64.00	79.00	67.00	43.00	13.00	48.90	30.20	42.8
2 x 1 1/2	76.00	86.00	83.00	55.00	16.00	61.35	34.70	48.90
2 1/2 x 2	92.00	92.00					53.50	
3 x 2 1/2	108.00	108.00					64.20	
4 x 3	140.00	121.00					79.50	

Medias cuplas

## Medias cuplas

### Tabla de medias cuplas Serie 3000- Roscado y SW

Tamaño		A Roscado	B Roscado	A SW	B SW	D Min.	F Max.	H Max.
pulg.	mm	mm	mm	mm	mm	mm	mm	mm
1/8	3.20	16.00	16.00	17.00	27.00	10.00	10.90	7.60
1/4	6.40	19.00	17.50	22.00	27.00	10.00	14.35	10.00
3/8	9.50	22.00	19.00	25.40	29.00	10.00	17.80	13.30
1/2	12.70	29.00	24.00	31.70	34.00	10.00	21.95	16.60
3/4	19.00	35.00	25.50	38.10	38.00	13.00	27.30	21.70
1	25.40	44.40	30.00	44.40	44.00	13.00	34.05	27.40
1 1/4	31.80	57.00	33.50	57.00	45.00	13.00	42.80	35.80
1 1/2	38.00	64.00	39.50	64.00	47.00	13.00	48.90	41.70
2	51.00	76.00	43.00	83.00	59.00	16.00	61.35	53.50
2 1/2	63.50	92.00	46.00	92.00	61.00	16.00	74.20	64.20
3	76.00	108.00	54.00		63.00	16.00	90.15	79.50
4	102.00	140.00	60.50		69.00	19.00	115.80	103.80

### Tabla de medias cuplas Serie 6000 - Roscado y SW

Tamaño		A Roscado	B Roscado	A SW	B SW	D Min.	F Max.	H Max.
pulg.	mm	mm	mm	mm	mm	mm	mm	mm
1/8	3.20	22.00	16.00	19.00	27.00	10.00	10.90	4.80
1/4	6.40	25.00	17.50	24.50	27.00	10.00	14.35	7.10
3/8	9.50	32.00	19.00	29.00	29.00	10.00	17.80	9.90

Tamaño		A Roscado	B Roscado	A SW	B SW	D Min.	F Max.	H Max.
pulg.	mm	mm	mm	mm	mm	mm	mm	mm
1/2	12.70	38.00	24.00	35.00	34.00	10.00	21.95	12.50
3/4	19.00	44.00	25.50	41.20	38.00	13.00	27.30	16.30
1	25.40	57.00	30.00	50.80	44.00	13.00	34.05	21.50
1 1/4	31.80	64.00	33.50	57.00	45.00	13.00	42.80	30.20
1 1/2	38.00	76.00	39.50	67.00	47.00	13.00	48.90	34.70
2	51.00	92.00	43.00	83.00	59.00	16.00	61.35	43.60
2 1/2	63.50	108.00	46.00		61.00	16.00	74.20	
3	76.00	127.00	54.00		63.00	16.00	90.15	
4	102.00	159.00	60.50		69.00	19.00	115.80	

**Trabajamos con las normas**

**ANSI B16.11 • ANSI B2.1 (NPT - WHITWORTH GAS BSPT) - API SB**

**Relacionados con Cuplas**

**Caños Epoxi**

**Tubos sin costura**